

JET 620

FRONTLIT 560 g/m²



FLAME RETARDANT

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: neon sign / backlit advertising / lightbox

PRODUCT PACKAGING

WIDE FORMAT	1.37m / 1.62m	Rolls of: 30 lm
SUPER WIDE FORMAT	3.20 m	Rolls of: 60 lm

PRODUCT CHARACTERISTICS

WEIGHT	560 g/m ²
BASE CLOTH	High tenacity polyester 1100 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin Inkjet lacquer One side
COLOUR	White 7348
THICKNESS	0.49 mm
TRANSLUCENCY XPT 54 199	23 %
TENSIBLE STRENGTH NF EN ISO 1421	210 / 200 daN
TEAR STRENGTH DIN 53363	25 / 20 daN
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	9 daN / 5cm
FIRE RETARDENT	M2 / B1 NFPA 701

Average values +/- 10%



SYSTEM
LOWICK



Certified for
HP Latex Inks