

JET 530

FRONTLIT 560 g/m²



FLAME RETARDANT

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: banners / signage / POS / indoor advertising

PRODUCT PACKAGING

WIDE FORMAT	1.06m / 1.37m 1.62m	Rolls of: 30 lm
SUPER WIDE FORMAT	3.20m	Rolls of: 60 lm

PRODUCT CHARACTERISTICS

WEIGHT	560 g/m ²
BASE CLOTH	High tenacity polyester 1100 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin Inkjet lacquer One side
COLOUR	White 7325
THICKNESS	0.47 mm
TRANSLUCENCY XPT 54 199	6 %
TENSILE STRENGTH NF EN ISO 1421	210 / 200 daN
TEAR STRENGTH DIN 53363	25 / 20 daN
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	7 daN / 5cm
FIRE RETARDENT	M2 / B1

Average values +/- 10%



SYSTEM
LOWICK



GRAPHIC FABRICS 2019



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001



www.dickson-coatings.com
www.evergreen-fabrics.com