

# OPTIKA PRINT

## MESH 300 g/m<sup>2</sup>



FLAME RETARDANT

### APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent UV and Latex inks
- INDOOR / OUTDOOR: scaffolding building wraps / decoration (stands / shops) / false ceilings

### PRODUCT PACKAGING

<b>SUPER WIDE FORMAT</b>	3.20 m	Rolls of: 50 lm
--------------------------	--------	-----------------

### PRODUCT CHARACTERISTICS

<b>WEIGHT</b>	300 g/m <sup>2</sup>
<b>BASE CLOTH</b>	High tenacity polyester 1100 Dtex
<b>COATING</b>	PVC coating
<b>FINISH</b>	Inkjet lacquer One side
<b>COLOUR</b>	White
<b>THICKNESS</b>	0.45 mm
<b>TRANSLUCENCY</b> XPT 54 199	19,5 %
<b>TENSIBLE STRENGTH</b> NF EN ISO 1421	140 / 180 daN
<b>TEAR STRENGTH</b> DIN 53363	30 / 30 daN
<b>TEMPERATURE STABILITY</b>	-30°C to +70°C -22°F to +158°F
<b>ADHESION</b> NF EN ISO 2411	6 daN / 5cm
<b>FIRE RETARDANT</b>	M1



Average values +/- 10%