

JET 520

FRONTLIT 550 g/m²



FLAME RETARDANT

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: banners / signage / POS / indoor communication

PRODUCT PACKAGING

WIDE FORMAT	1.06 m / 1.37 m / 1.62 m / 3.20 m	Rolls of: 30 lm
SUPER WIDE FORMAT	2.50 m / 3.20 m	Rolls of: 60 lm

PRODUCT CHARACTERISTICS

WEIGHT	550 g/m ²		
COATING	PVC coating System LOWICK	Base cloth	High tenacity polyester 1100 Dtex
COLOUR	White 7325	Finish	Satin Inkjet lacquer One side
THICKNESS	0.45 mm	Translucency XPT 54 199	6 %
TENSILE STRENGTH NF EN ISO 1421	210 / 200 daN	Tear strength DIN 53363	25 / 20 daN
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F	Adhesion NF EN ISO 2411	7 daN / 5cm
FIRE RETARDENT	M1		

Average values +/- 10%



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001

www.dickson-coatings.com
www.evergreen-fabrics.com