

JET 550

FRONTLIT 560 g/m²

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: billboards / banners / signage / POS / pole banners

PRODUCT PACKAGING

| | | |
|-------------------|--|--|
| WIDE FORMAT | 0.76 m / 1.06 m / 1.37 m / 1.62 m 2.50 m / 3.20 m | Rolls of: 30 lm |
| SUPER WIDE FORMAT | 2.50 m / 2.78 m / 3.20 m | Rolls of: 60 lm (250 lm on request) |

PRODUCT CHARACTERISTICS

| | | | |
|------------------------------------|-----------------------------------|----------------------------|--------------------------------------|
| WEIGHT | 560 g/m ² | | |
| COATING | PVC coating System LOWICK | Base cloth | High tenacity polyester 1100 Dtex |
| COLOUR | White 7325 | Finish | Satin Inkjet lacquer One side |
| THICKNESS | 0.47 mm | Translucency XPT 54 199 | 6 % |
| TENSILE STRENGTH NF EN ISO 1421 | 210 / 200 daN | Tear strength DIN 53363 | 25 / 20 daN |
| TEMPERATURE STABILITY | -30°C to +70°C -22°F to +158°F | Adhesion NF EN ISO 2411 | 7 daN / 5cm |
| FIRE RETARDENT | DIN 75 200 NFPA 701 | | |

Average values +/- 10%



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001

www.dickson-coatings.com
www.evergreen-fabrics.com