

LACOPAC

BLACKOUT 680 g/m²



FLAME RETARDANT



NO CURLING

APPLICATIONS

- BOTH SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR COMMUNICATION: signage / banners / POS / hanging banners

PRODUCT PACKAGING

WIDE FORMAT	1.02 m / 1.37 m / 3.10 m	Rolls of: 30 lm
SUPER WIDE FORMAT	3.10 m	Rolls of: 60 lm

PRODUCT CHARACTERISTICS

WEIGHT	680 g/m ²		
COATING	PVC coating System LOWICK	Base cloth	High tenacity polyester 550 Dtex
COLOUR	White 7326	Finish	Satin inkjet lacquer Both side
THICKNESS	0.49 mm	Translucency XPT 54 199	0 %
TENSILE STRENGTH NF EN ISO 1421	180 / 150 daN	Tear strength DIN 53363	20 / 20 daN
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F	Adhesion NF EN ISO 2411	7 daN / 5cm
FIRE RETARDENT	M2 / B1 B-s2-d0 (EN 13 501-1) NFPA 701		

Average values +/- 10%



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001

www.dickson-coatings.com
www.evergreen-fabrics.com