

# OPTIKA PRINT

## MESH 300 g/m<sup>2</sup>



FLAME RETARDANT

### APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent UV and Latex inks
- INDOOR / OUTDOOR: scaffolding / decoration (stands / shops) / false ceilings

### PRODUCT PACKAGING

SUPER WIDE FORMAT	3.20 m	Rolls of: 50 lm
-------------------	--------	-----------------

### PRODUCT CHARACTERISTICS

WEIGHT	300 g/m <sup>2</sup>		
COATING	PVC coating	Base cloth	High tenacity polyester 1100 Dtex
COLOUR	White	Finish	Inkjet lacquer One side
THICKNESS	0.45 mm	Opening factor	19.5%
TENSILE STRENGTH NF EN ISO 1421	140 / 180 daN	Tear strength DIN 53363	30 / 30 daN
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F	Adhesion NF EN ISO 2411	6 daN/5cm
FIRE RETARDENT	M1		

Average values +/- 10%



Company with management system certified by DNV-GL  
ISO 9001 · ISO 14001

[www.dickson-coatings.com](http://www.dickson-coatings.com)  
[www.evergreen-fabrics.com](http://www.evergreen-fabrics.com)