

JET 550

FRONTLIT 560 g/m²

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: billboards / banners / signage / POS / pole banners

PRODUCT PACKAGING

WIDE FORMAT	0.76m / 1.06m 1.37m / 1.62m 2.50m / 3.20m	Rolls of: 30 lm
SUPER WIDE FORMAT	2.50m / 2.78m 3.20m	Rolls of: 60 lm (250 lm on request)

PRODUCT CHARACTERISTICS

WEIGHT	560 g/m ²
BASE CLOTH	High tenacity polyester 1100 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin Inkjet lacquer One side
COLOUR	White 7325
THICKNESS	0.47 mm
TRANSLUCENCY XPT 54 199	6 %
TENSIBLE STRENGTH NF EN ISO 1421	210 / 200 daN
TEAR STRENGTH DIN 53363	25 / 20 daN
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	7 daN / 5cm
FIRE RETARDENT	DIN 75 200 NFPA 701

Average values +/- 10%



SYSTEM
LOWICK



Certified for
HP Latex Inks